



\*\* LARGE \*\*

**ES 350 F**

Capacity tons **35**

PRODUCT	CORN	WHEAT & BARLEY	SUNFLOWER	RAPE & SOY	RICE
INOX SCREEN	2,5	2,5	2,5	1,5	1,5
BURNER TEMPERATURE	120°	100/105°	65/70°	75/80°	45°
PRODUCT TEMP.	55/63°	45/48°	40/45°	40/45°	28/35°
PS	0,75	0,78	0,55	0,65	0,58
CAPACITY ON TONS	34,5	35,88	25,3	29,9	26,68
CAPACITY ON MC	46	46	46	46	46

LOAD TIME	CORN	WHEAT & BARLEY	SUNFLOWER	RAPE & SOY	RICE
	20'	20'	20'	20'	45'
<b>DRYING</b>	1½ h.	1½ h.	1¾ h.	1¾ h.	5 h.
	5 lt /t. n. 6½	4 /4,5 lt /t. n. 7½	5/6 lt /t. n. 7	4/5 lt /t. n. 7	4 lt /t. n. 3¼
	2½ h.	2½ h.			
	10 lt /t. n. 5½	8/9 lt /t. n. 5½			
	3½ h.	3 h.			
	14 lt /t. n. 4½	10/11 lt /t. n. 5¼			
COOLING TIME	1¼ h.	1 h.	1 h.	1 h.	45'
UNLOAD TIME	17'	17'	20'	17'	45'

POWER required for:

Tractor drive PTO hp	120	120	120	120
Electric drive kw	65	65	65	65

Burner	kcal/h	1300000
Fan	Diameter	1000 mc/h 85000


<b>DIAMETER</b>	mt.	<b>4,02</b>
HEIGHT DURING TRANSPORT	mt.	4,55
HEIGHT OF CYLINDER	A mt.	6,2
OPERATING HEIGHT	B mt.	6,85

ESMA SRL - VIA VEGRI, 36 - MONTEGALDA (VI) ITALIA  
 Tel. 0039 0 444 412511 Fax 0039 0 444 413230  
[www.esma.it](http://www.esma.it) skype esmasrl



mailto: [info@esma.it](mailto:info@esma.it)

OPERATING HEIGHT with dust	C	mt.	6,85
HEIGHT OF OUTLET CHUTE	D	mt.	4,07
LENGHT	E	mt.	7,15
LENGHT with 2,60mt loading hopper	F	mt.	10,8
LENGHT with loading auger	G	mt.	10,8
HEIGHT with electric outlet auger		mt.	
TANK		lt	
WHEELS			4
DIAMETER OF LOADIN AUGER		mm	300
DIAMETER OF CENTRAL SCREW CONVEYOR		mm	450



The manufacturing company may vary the data without notice. The data relevant to yields are just an indication. These can change considerably according to the environment conditions (temperature, moisture, etc) and the product characteristics (ripening degree, cleaning, etc.) Important differences are possible among the different varieties of the same product.